

LEDiFFERENT[®]

广东非同凡想照明电器有限公司

GD LEDifferent Lighting Electrical Appliance Tech Co., LTD



Specification

规格

Product Unit Parameters

Type 型号	RT31.25A	RT50B
Pixel compose 像素组成	1R1G1B	2R2G2B
LED	DIP346	DIP346
Pitch	31.25mm	50mm
Dimension 尺寸	L:1000mm-2000mm	L:1000mm-2000mm
resolution ratio 分辨率	32 点	20 点
direction 方向	Vertical /Horizontal 垂直/水平	Vertical/ Horizontal 垂直/水平
Brightness 亮度	6.5cd/ Pixel 6.5cd/像素	13cd/ Pixel 13cd/像素
Net Weight 净重	0.4KG/m	0.4KG/m
Max Consumption 最大功率	9W/m	15W/m
View angle 视角	H100° /V45°	H100° /V45°
Protection Grade 防护等级	IP67	IP67
Tube structure 灯管结构	1 columns 1 列	1 columns 1 列
Tube width 灯管宽度	14.5mm	16mm
Connection dot 元件连接点	1024点 (60Hz) ; 32m	
Heat dissipation 散热器	Convective heat dissipation 对流散热	
Wind dissipation 风散热	Level 12 12 级	
Power supply 电源	Power supply with PFC PFC 电源	
Installation 安装	Fast install 快速安装	
Fire safety 消防安全	10S/unit	
Fire resistance 防火性	Full V0 grade 完整的签证官级	
Service 服务	Front、Black 前后服务	
Driver Mode 驱动方式	Static Current, Build-in PWM 静态电流, 内置 PWM	
Color Tem. 色温	3200-9300K	
Refresh Rate 刷新率	≥2000 Hz	
Refresh rate 刷新率	≥60Hz	
Running Tem. 工作温度	-40℃ to 60℃	
Store Tem. 储存温度	-55℃ to 120℃	
Life time 寿命	≥100,000 hours	
Input Voltage 输入电压	48V	
Gray Scale 灰度	16bit	
Seismic capability 抗震能力	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes 10 ~ 500Hz, 5G 12 分钟/周期, 周期为 72min. 沿着 X 轴, Y 轴, Z 轴	
EMC 电磁兼容性	Conduction Emission EN55022 CLASS-A、Harmonic Current IEC61000-3-2 Class-A 导电发射 EN55022 A 级, 谐波电流 IEC61000-3-2 A 级	